



"Let your building breathe "

Breathable Membranes for Rainscreen Wall and Sloped Roof Systems



SRP AirOutshield™ UV

Breathable Underlayment for Open Joint, Rain Screen Wall Systems

Description

A double layer, coated polyester, water and ultra violet light (UV) resistant, breathable underlayment for open joint rain screen wall systems.

Uses

As a secondary drainage plane, sheathing membrane or air barrier behind rain screen wall cladding systems including siding (wood, fibre cement, metal, brick) and shingles (metal, copper, zinc, cedar). Especially suited for use in cladding systems where the membrane will be visible and resistance to long term UV exposure is needed.

Features/Benefits

- High Breathability Rate- *Allows moisture within the wall system to dry rapidly, thereby reducing potential for mould, mildew, rot, metal corrosion and reduced insulation thermal values.*
- UV Resistant- *Resists UV that penetrates through cladding systems. Tested in accordance with the stringent DIN EN 13859 - 1 European standard which includes testing before and after exposure.*

Water Resistant- Moisture entering the wall system is quickly diverted before it can damage insulation and other components.

- Durable- *Tear, rip and puncture resistant which reduces repairs and related labour costs.*
- Polyester- *Provides superior resistance to the high temperatures associated with typical dark coloured cladding systems.*
- Black- *Provides enhanced aesthetics for open joint cladding systems.*

Packaging

Roll size: 1.5m W x 50m L (59" W x 164' L)

Weight: 20.3 kg (44.7 lbs)

Colour: Exterior side- Coated Black, Interior side- Black

System Accessories

SRP 1" D.S. Seam Tape: Roll size 25mm x 15.24m (1" x 50')

SRP 100 UV Tape: Roll size 100mm x 25m (4" x 81')

SRP 60 UV Seam Seal Tape: Roll size 60 mm X 25m (2.4" X 81')

SRP AirOutshield™ UV **SRP Canada Inc.**

www.srpcanada.ca

1-866-533-0233



"Let your building breathe "

Breathable Membranes for Rainscreen Wall and Sloped Roof Systems

Compliances

Accepted as an underlay by wall system manufacturers. Consult SRP and your system manufacturer.

Physical Properties

	Test Method	Result
Colour		Black Coated (top) Black textured (Bottom)
Nominal Weight		270 g/m ²
UV Resistance	DIN EN 13859	5,000 hours exposure with a reduction in tensile strength of less than 5%
Cold Temperature Bending	EN 1109	-50°C
Water Vapour Transmission	ASTM E96, Method A	1537 ng/Pa/s/m ² (26.9 perms)
Air Permeance	ASTM E2178	0.0005 L/s.m ² (0.0001 cfm/ft ²) @75 Pa
Fire Classification	ASTM E 84-13a	Class 1 or A (FS <25, SD <450)

Installation

For complete instructions refer to the detailed installation guide available at www.srpcanada.ca. SRP AirOutshield UV is installed under the primary wall cladding material with the smooth black (coated) side facing out. Install to form a continuous membrane over the entire wall area and to allow water to drain away from openings and penetrations. Ensure there are no blockages that may obstruct the water flow.

Precautions/Limitations

AirOutshield UV is not recommended for applications where more than 40 % of the product will be exposed to UV or where joints are greater than 50mm in width. Do not use under asphalt shingles or in roofing. Install cladding system within 120 days from installation of AirOutshield UV.

Technical Assistance

SRP Canada Inc. 1-866-533-0233,
www.srpcanada.ca

SRP AirOutshield™ UV **SRP Canada Inc.**

www.srpcanada.ca

1-866-533-0233



"Let your building breathe "

Breathable Membranes for Rainscreen Wall and Sloped Roof Systems

Short Form Specification (visit www.srpcanada.ca for detailed specification)
Breathable, UV Resistant underlayment for open joint rain screen wall systems: Coated, spun bonded polyester, breathable membrane with a nominal weight of 270g/m², tested to DIN EN 13859-1 for 5,000 hours exposure with less than 5% reduction in tensile strength. SRP AirOutshield UV breathable by SRP Canada, 1-866-533-0233, www.srpcanada.ca

Warranty

The information, and in particular, the recommendations relating to the application and end-use of SRP Canada products, are given in good faith based on SRP Canada's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request or can be accessed in the Internet under www.srpcanada.ca.

Issued: 2015-04-07

SRP AirOutshield™ UV **SRP Canada Inc.**

www.srpcanada.ca

1-866-533-0233