



Breathable Membranes for Rainscreen Wall and Sloped Roof Systems

SRP-Eternabond 1" D.S. "Double Stick" Seam Tape

Basic Use

This self sealing adhesive creates a water tight, conformable seal between layers of SRP Roofshield, SRP Wallshield, SRP AirOutshield, SRP AirOutshield ROOF and at junctions with other materials.

Composition

DoubleStick Tape utilizes EternaBond's advanced MicroSealant™ Technology, a 100% solids formulation of synthetic resins, thermoplastics, non-curing rubbers (not butyl), with a built in primer, sandwiched between two siliconized release liners.

Technical Data

Standard roll sizes 1" X 50'
Total thickness standard is 30mils
Adhesion 19lbs/in width
Low temp flexibility Excellent
Application temp. range -25°F - > 150°F
Temperature range -70°F - >200°F
Pliability No cracks in membrane
Water vapor test (ASTME 96B) .005 grms/100" sq./24hrs/100°F
Permanence .001 perms maximum
Elongation >500%
Shelf life Up to 5 years

Surface Preparation

Surface must be clean and dry. Moisture, dust, dirt, and other foreign matter should be removed. Remove oil, grease, and etc. with a suitable cleaner.

Application

To apply the DoubleStick, remove the release liner on one side of the DoubleStick and apply to the surface to be bonded. Remove the 2nd release liner, apply pressure using a small seam roller or similar to fully bond tape to the surfaces.

SRP Canada Inc.

www.srpcanada.ca

1-866-533-0233

Updated 2009-04-01